Baton Rouge Industries, Inc.

5319 Groom Road • P.O. Box 26 Baker, Louisiana 70714 1-800-232-0334 • 225-775-3362 FX 225-775-3498

BatonRougeIndustries.com

L-628

Power Gear E.P. Gear Lubricant GL-4

Red Dye added for leak traceability w/moly

(API GL-4 90W140)

DESCRIPTION

L-628 Power Gear E.P. Gear Lubricant GL-4 w/moly gear oil is a multi-service EP gear lubricant manufactured with high quality base stocks and superior additive technology. They are recommended for use in gear boxes, manual transmissions, bearings, gear reducers and many other applications where API service classification GL-4 gear lubricant is specified. This product can also be used for make-up of limited slip/positive traction rear axels.

INDUSTRY SPECIFICATIONS

- API MT-1
- API GL-4
- MIL-PRF-2105E
- PG-2 Limited slip
- Long service life
- Non-foaming
- Non-corrosive
- Anti-wear
- Extreme pressure
- Limited slip
- Tackifiers
- Rust inhibitors
- * ALWAYS CONSULT YOUR OWNER'S MANUAL FOR THE PROPER FLUID FOR YOUR EQUIPMENT.

TYPICAL TEST DATA

SAE GRADE	GL-4 90W140
Specific Gravity @ 60 °F	0.8925
Viscosity, Kinematic	
cSt at 40°C	367.2
cSt at 100°C	27.44
Viscosity Index	101
Viscosity, Brookfield	
cP at -12°C Max	150,000
Flash Point, °F	415
Pour Point, °C (°F)	-15 (5)
Color	red

Typical test data are average values only. Minor variations which do not affect product performance are to be expected during normal manufacturing.

For Product Information Sheets and Safety Data Sheets, please visit our website: BatonRougeIndustries.com